


Optical wave network system and method of monitoring a network trouble

Patent Number: EP0907266
Publication date: 1999-04-07
Inventor(s): TAKESHITA HITOSHI (JP); HENMI NAOYA (JP)
Applicant(s): NIPPON ELECTRIC CO (JP)
Requested Patent: ☐ EP0907266
Application Number: EP19980117435 19980915
Priority Number(s): JP19970268253 19970916
IPC Classification: H04J14/02; H04L1/22; H04B10/213
EC Classification: H04J14/02M
Equivalents: ☐ JP11098077, ☐ US6407834
Cited Documents:

Abstract

Optical regenerative relay amplifier (102) have a function for monitoring strengths of optical signals from an optical fibers (101), and issuing optical signal trouble detection signal (AIS (Alarm Indication Signal)) for shutting down optical strengths in case that optical signal inputs are lost, and notifying the trouble, and optical ADMs (103) have a wavelength path selecting function, a wavelength path bundle function, and a wavelength path trouble or quality monitoring function in addition to an AIS issue function, and the optical cross-connect systems (104) have an AIS issue function, a function for monitoring a trouble or quality of optical signals every wavelength path, a wavelength path grooming function, and a wavelength path protection function, and the terminal stations (105) transmit and receive services by optical signals having predetermined wavelengths, and monitoring a trouble or quality of optical signals every wavelength path is conducted without depending on signal speed and format. 

Data supplied from the esp@cenet database - I2